



NexStor JRS-E0X2 SAS SATA Storage Enclosure

The NexStor JRS-E0X2 SAS Storage Enclosure offers the latest JBOD storage expansion with generous expansive capabilities that allows you to deploy both SAS and SATA drives in a single enclosure.

Seamless Capacity Expansion

The NexStor JRS-E0X2 SAS SATA JBOD Enclosure provides the latest JBOD storage expansion for NexStor Storage Servers as well as external DAS storage for servers and appliances. The JRS-E0X2 offers single and dual channel options supporting 6GB SAS and SATA SSDs and HDD drives.

Exceptionally High Storage Density While Leveraging High-Efficiency Power

The NexStor JRS-E0X2 maximizes storage capacity in a 2U form factor by offering 24 hot-swap 2.5" SAS/SATA hard drive bays for applications requiring extra storage; optimizing every aspect of interior space without compromising superior cooling capabilities. The NexStor JRS-E0X2 is equipped with a redun-

dant 1200W high-efficiency (80%+) power supply for outstanding power savings, with specially designed optimized cooling,

Resource Optimized Just for You

The NexStor JRS-E0X2 Server boasts industry leading performance-per-Watt/per-Dollar on the market and helps your business to meet workload demands with superb stability, efficiency and long term business value.

NexStor JRS-E0X2 SAS SATA Storage Enclosure

Host Connections	Single or Dual 6Gb SAS III Expander Host Channels
Expansion Connections	Single or Dual 6Gb SAS III Expander Cascading Expansion Channels
Maximum Number of Drives	Up to 24x 2.5" SSD, SAS or SATA HDD's per Enclosure
System Expansion	Cascade up to 7x NexStor JRS-E0X2 2U24 2.5" SAS/ SATA HDD, SDD Expansion Enclosures per SAS Host Channel
Maximum External Storage	Up to 168x 2.5" SSD, SAS, or SATA HDD's per SAS Host Channel
Dimensions (H x W x D)	3.5" x 17.2" x 24.8" (89mm x 437mm x 630mm)
Power Supply	Dual Hot Swap 1200W 80+ High Efficiency
Ventilation	4 x 40 x 28mm High-Efficiency Fans
Operating Temp	Operating Temperature: 10° to 35° C (50° to 95° F) Non-Operating Temperature: -40° to 70° C (-40° to 158° F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-Operating Relative Humidity: 5 to 95% (non-condensing)
Form Factor	2U Rackmount Server Chassis



Innovation Delivered.

7669 Limestone Drive
Gainesville, VA 20155

Toll-Free: 1 (888) RING-NCS

Voice: (703) 743-8500 / Fax: (703) 621-1701

www.ncst.com

Actual functionality may be limited to other factors, including type, number and capabilities of optional modules incorporated. NCS may make changes to product specifications at any time and without notice. The information in this document is for informational use only, is subject to change without notice. NCS assumes no responsibility or liability for any errors or inaccuracies that may appear. All names are provided for informational use only. Other brands and names may be claimed as property of their respective owners.

SPEC-JRS-E0X2-04-092012