

PORT BAR II



Key Features

- For Atlas L2, L3 and S1 Series Notebooks
- 68-pin Port Bar II I/O Connector
- One 10/100 MHz RJ-45 LAN port
- One EPP/ECP Parallel Port/D-sub 25-pin
- One PS/2 port for keyboard/mouse
- Two USB Ports
- One VGA Port/D-Sub 15-pin for external monitor
- Separately 60W/50W DC-in jack and power supply to main unit through a cable interface
- Dimensions:
200 x 160 x 37 mm/7.87 x 6.29 x 1.45 inches

Port Bar II Port Replicator



VGA

PS2

USB 2.0

USB 2.0

RJ-45

Parallel

DC-in Jack

The NCS Port Bar II optimizes valuable desktop real estate by providing an easy one-step connectivity solution whether at home or in the office. The convenience of a centrally located hub attached to a full sized CRT monitor, 10/100 Ethernet LAN connectivity, laser jet printer, as well as a multitude of USB 2.0 peripheral devices such as PDAs, Flash memory readers, digital cameras, and scanners is an absolute must for the earnest mobile Road Warrior. The Port Bar II offers the expedience of having a pass through for power, VGA port, PS-2 port, RJ-45 port, parallel port, and two USB ports, thus eliminating the hassle of adding each component device one-at-a-time. The Port Bar II is "Hot-dockable," having a universal Plug & Play feature, permitting it to be connected or disconnected to the Atlas notebook while in the ON or OFF state.

