



Gemini CT2-A425 Desktop

The Gemini CT2-A425 is the perfect blend of form and function in an ultra-compact form factor that boasts surprisingly generous expansive capability.

Great Things Do Come in Small Packages

The Gemini CT2-A425 is a reliable workhorse that supports the Intel® 3rd/2nd generation Core™ i7/i5/i3/Pentium®/Celeron® processors in the LGA1155 package, delivering an automatic speed boost when you need it most; multi-way processing that lets you get more done faster and easily adapts to your needs. Additionally, the Gemini CT2-A425 features integrated Intel® Smart Connect Technology, which boasts auto application refresh, less waiting time, and can receive web updates with fresh content for selected applications, even when the system is in sleep mode. This means less time waiting for applications to update and sync with the cloud, leading to a more efficient computing experience.

Sleek & Tidy Form Factor

The Gemini CT2-A425's sleek and space-saving construction fits neatly in tight corners and helps to reduce desktop clutter.

Excellent Video Quality Already Included

Powered by the Intel® H61 Express Chipset, the Gemini CT2-A425 is equipped with DVI-D and VGA ports to support flexible, dual independent display

for processors with integrated Intel® HD Graphics delivering superb visual performance for sharper images, richer color, and lifelike video (without the extra expense of add-in video cards or decoders).

All You Need to Keep You Connected

With a score of the latest I/O ports (including six USB 2.0 ports and a DVI port), the Gemini CT2-A425 makes it simple to connect to peripheral, communication and consumer electronic devices.

Ready & Willing

The Gemini CT2-A425 is also Windows® 8 ready, so Gemini runs faster, is more secure and more reliable, which can aid in maintaining high office productivity.

Gemini CT2-A425 Desktop

Processor	LGA 1155 Socket Intel® 2nd & 3rd Generation Core™ i3/i5/i7 Processors Intel® Pentium® Dual-Core and Celeron® Processors
Chipset	Intel® H61 Express Chipset
System Memory	2x DIMMs, DDR3 1600/1333/1066 MHz Non-ECC, Unbuffered Memory Maximum Memory Capacity of 16GB
Integrated SATA/RAID	4x SATA 3Gb/s Ports
Integrated Video	Integrated Graphics Processor - Supports DVI With Max. Resolution 1920 x 1200 @ 60 Hz - Supports RGB with max. resolution 2048 x 1536 @ 75 Hz Supports Intel® HD Graphics, Quick Sync Video
Integrated Audio	Integrated 6-Channel (5.1) HD Audio via Realtek CODEC Front Panel Connectors: Headphone & Microphone In Back Panel Connectors: Line-in, Line-out and Microphone-in
Integrated Super I/O	1x PS/2 Keyboard/Mouse Combo Port(S) 1x DVI Port 1x D-Sub Port 1x LAN (RJ45) Port 6x USB 2.0 Ports (2x in the front, 4x in the rear) 3x Audio Jacks
Integrated Gigabit	Integrated Realtek® 8111F PCIe Gigabit LAN Controller (10/100/1000 Mbps/sec)
Expansion Slots	1x PCIe 3.0/2.0 x16 Slot, 2x PCIe 2.0 x1 Slots, 1x PCI Slot
Drive Bays	1x Internal 3.5" HDD, 1x External Slim ODD and 1x Optional Card Reader
Security	TPM 1.2
Dimensions (H x W x D)	Vertical: 12.8" x 3.5" x 12.75"; 325mm x 89mm x 324 mm Horizontal: 12.75" x 12.8" x 3.5" , 324mm x 325mm x 89mm
Power Supply	Input Voltage 100-127 VAC/200-240 VAC Input Frequency 50/60 Hz Maximum Output 300 Watts Form Factor TFX Active PFC
Environmental	Operating Temperature 0° to 35° C / 32° to 95° F Storage Temperature -40° to 70° C / -42° to 158° F Relative Humidity 92% RH @ 36° C / 97° F
Regulatory & Product Certifications	EMI/RFI: FCC Declaration of Conformity (DoC) Safety: Underwriter Laboratories (UL) 60950, 3rd Edition EPA: Energy Star Compliant; EPEAT Silver Compliant Other: NIST BIOS SP 800-147
Fans	1x 60 mm Cooling Fan



7669 Limestone Drive
Gainesville, VA 20155
Toll-Free: 1 (888) RING-NCS
Voice: (703) 743-8500 / Fax: (703) 621-1701
www.ncst.com

Actual functionality may be limited to other factors, including type, number and capabilities of optional modules incorporated. NCS may make changes to product specifications at any time and without notice. The information in this document is for informational use only, is subject to change without notice. NCS assumes no responsibility or liability for any errors or inaccuracies that may appear. All names are provided for informational use only. Other brands and names may be claimed as property of their respective owners.

DS-CT2-A425-01-110912