



The NexServ ARN-72D1 Server features high-performance and reliability to efficiently support the workloads of today's software-defined datacenter

Optimized Power and Scalability To Better Support the Demands of Existing And Future Datacenter Applications

The NexServ ARN-72D1 Server features industry-leading memory bandwidth supporting up to 4TB of the latest DDR4 memory, 10 NVMe/SATA3 drive bays, up to 64 GB of DDR4 memory in 4 UDIMM slots, quad Gigabit Ethernet LAN, and PCIE 3.0 technology. Powered by AMD's EPYC™ 7000-Series, the ARN-72D1 makes it possible for cloud environments to drive greater scale and performance. Virtualized datacenters can further increase consolidation ratios while delivering better performing virtual machines and Big Data, and analytics environments can collect and analyze larger data sets much faster. High performance applications in research labs can solve complex problem sets in a significantly accelerated manner.

Latest Technology and Remote Monitoring

As the leader in providing our valued customers the best in-market, NCS is proud to offer the latest technology to support your latest software applications and deliver longer life cycle support. The ARN-72D1 is also equipped with an enhanced KVM over LAN feature so you can manage the appliance remotely.

Resource Optimized Just for You

The ARN-72D1 Server boasts industry leading performance-per-Watt/per-Dollar on the market and helps your business to meet workload demands with superb stability, efficiency and long term business value.

ARN-72D1 Server

Form Factor

- 1U rack mount

Processor

- Supports AMD EPYC 7000-Series processors
 - Up to 32 Cores

Processor Sockets

- 2x sockets

Chipset

- System on chip (SOC)

Memory

- Supports up to 4TB DDR4 ECC Memory (RDIMM or LRDIMM) in 32 DIMM Slots; Up to 2666MHz

Drive Bays

- 10x 2.5" SATA/SAS HDD bays with optional NVMe support

Integrated I/O

- Onboard NICs: Quad Gigabit Ethernet LAN ports
- USB Connectors: 2x USB 3.0 ports (rear)
- 1x VGA Port
- 1x Dedicated LAN port for IPMI

Expansion Slots

- 2x PCI-E Gen 3.0 x16 slots (2 full height)
- 1x PCI-E GEN 3.0 x8 slot (low profile)
- 1x PCI-E GEN 3.0 x8 slot (internal)

Power Supply

- 1000W redundant power supplies (titanium level)

Dimensions (H x W x D)

- 1.7" x 17.2" x 27.8"
- 43.18mm x 436.88mm x 706.12mm

Fans

- 8x heavy duty fans w/ optimal fan speed control

Environmental

- Operating temperature: 10° to 35° C / 50° to 95° F
- Storage temperature: -40° to 70° C / -40° to 158° F
- Relative humidity: 8% to 90% (non-condensing)
- Non-operating relative humidity: 5% to 95% (non-condensing)



NCS Technologies, Inc. • 7669 Limestone Drive, Gainesville, Virginia 20155-4038
1 888 RING NCS (toll-free), 703 743 8500 (office), 703 743 8659 (fax) • www.ncst.com

Actual functionality may be limited to other factors, including type, number and capabilities of optional modules incorporated. NCS may make changes to product specifications at any time and

without notice. The information in this document is for informational use only, is subject to change without notice. NCS assumes no responsibility or liability for any errors or inaccuracies that may ap-

pear. All names are provided for informational use only. Other brands and names may be claimed as property of their respective owners.