



## The budget friendly NexServ XRB-3121 Server is designed to deliver solid performance and impressive reliability for customer applications

### **Suitable For a Wide Range of Uses for Small Business**

The NexServ XRB-3121 Server features up to 64 GB of DDR4 memory in 4 UDIMM slots, compact storage (two fixed 3.5" drive bays or three 2.5" drives), dual Gigabit Ethernet LAN, and PCIE 3.0 technology. Powered by Intel's Xeon E3-1200 V6/V5 processors, the XRB-3121 delivers a significant performance increase with a lightning fast architecture and world-class performance.

### **Latest Technology and Remote Monitoring**

As the leader in providing our valued customers the best in-market, NCS is proud to offer the latest technology to support your latest software applications and deliver longer life cycle support. The XRB-3121 is also equipped with an enhanced KVM over LAN feature so you can manage the appliance remotely.

### **Resource Optimized Just for You**

The XRB-3121 Server boasts industry leading performance-per-Watt/per-Dollar on the market and helps your business to meet workload demands with superb stability, efficiency and long term business value.

# XRB-3121 Server

## Form Factor

- 1U rack mount

## Processor

- Supports Intel Xeon E3-1200 V6/V5 processors
- Supports Intel 7th/6th Gen Core i3 processors

## Processor Sockets

- 1x socket

## Chipset

- Intel C236 Chipset

## Memory

- Supports up to 64GB DDR4 ECC memory (UDIMM) in 4 DIMM Slots; Up to 2400MHz

## Drive Bays

- 2x fixed 3.5" drive bays or 3x 2.5" drives option

## Integrated I/O

- Onboard NICs: Dual Gigabit Ethernet LAN ports
- USB Connectors: 2x USB 3.0 ports; 2x USB 2.0 ports (rear)
- 1x VGA Port
- 1x Dedicated LAN port for IPMI

## Expansion Slots

- 1x PCI-E Gen 3.0 x8 slot (full height)

## Power Supply

- 350W redundant power supplies (platinum level)

## Dimensions (H x W x D)

- 1.7" x 17.2" x 14.4"
- 43.18mm x 436.88mm x 365.76mm

## Fans

- 2x heavy duty fans w/ optimal fan speed control

## Environmental

- Operating temperature: 10° to 35° C / 50° to 95° F
- Storage temperature: -40° to 70° C / -40° to 158° F
- Relative humidity: 8% to 90% (non-condensing)
- Non-operating relative humidity: 5% to 95% (non-condensing)



NCS Technologies, Inc. • 7669 Limestone Drive, Gainesville, Virginia 20155-4038  
1 888 RING NCS (toll-free), 703 743 8500 (office), 703 743 8659 (fax) • [www.ncst.com](http://www.ncst.com)

Actual functionality may be limited to other factors, including type, number and capabilities of optional modules incorporated. NCS may make changes to product specifications at any time and

without notice. The information in this document is for informational use only, is subject to change without notice. NCS assumes no responsibility or liability for any errors or inaccuracies that may ap-

pear. All names are provided for informational use only. Other brands and names may be claimed as property of their respective owners.