



Stratus 7280 Desktop Series

With business-class performance and control, the Stratus 7280 Desktop Series is ready to tackle your most demanding business needs.

By harnessing the power of Intel's® breakthrough 4th generation i3, i5, i7 Core™, Pentium® or Celeron® Series Processors (LGA1150), the Stratus 7280 Desktop Series delivers more responsive multi-tasking, adaptable performance and built-in visual capabilities to bring more intelligent performance. The Stratus 7280 Desktop Series capabilities includes USB 3.0 Ports, SATA 6.0 Gb/s, Ethernet LAN, 4-channel DDR3 memory (up to 32GB), and PCI Express controllers to keep your business highly productive. With three convenient form factors to choose from (the MT, DT, & SFF) the Stratus 7280 Desktop Series gives you an infinite number of ways to customize a desktop to suit your exact requirements. Additionally, the Stratus Desktops' tool-less chassis offers simple and direct access to system components and upgrades.

Auto Application Refresh and Shorter Wait Times

The Stratus 7280 Desktop Series features Intel® Smart Connect Technology, allowing your desktop to receive web updates with fresh content for selected applications, even when the system is

in sleep mode. This means less time waiting for applications to update and sync with the cloud, leading to a more efficient computing experience.

Excellent Video Quality Already Included

The Stratus 7280 Desktop Series' integrated Intel® HD Graphics delivers superb visual performance for sharper images, richer color, and life-like video (without the extra expense of add-in video cards or decoders). Users have the ability to multitask on up to two independent displays through HDMI, DisplayPort, VGA, and DVI connectors. The Stratus 7280 Desktop Series' also supports AMD Quad-GPU CrossFireX™ Technology.

Ready & Willing

The Stratus 7280 Desktop Series is also Windows® 8 ready, so your desktop runs faster, is more secure and more reliable, which can aid in maintaining high office productivity.

Stratus 7280 Desktop Series

Available Form Factors	MT	DT	SFF
Processor	Intel® Socket 1150 for 4th Generation Core™ i7, i5, & i3, Pentium® and Celeron® Series Processors Supports Intel® 22 nm CPU; Supports Intel® Turbo Boost Technology 2.0 (dependent on CPU type)		
Chipset	Intel® B85 Express Chipset		
System Memory	4x DIMM, Max. 32GB, DDR3 1600/1333/1066 MHz Memory; Dual Channel Memory Architecture		
Integrated Video	Integrated Graphics Processor Multi-VGA Output Support : HDMI/DVI-D/RGB/DisplayPort Ports - Supports HDMI with Max. Resolution 4096 x 2160 @ 24 Hz / 2560x1600 @ 60 Hz - Supports DVI-D with Max. Resolution 1920x1200 @ 60Hz - Supports RGB with Max. Resolution 1920x1200 @ 60Hz - Supports DisplayPort with Max. Resolution 4096 x 2160 @ 24 Hz / 3840x1600 @ 60Hz Maximum Shared Memory of 1024 MB Supports AMD Quad-GPU CrossFireX™ Technology		
Integrated Audio	Realtek® ALC887-VD 8-Channel High Definition Audio CODEC Supports Jack-Detection, Multi-Streaming, Front Panel Jack-Retasking, Anti-Pop Function		
Integrated SATA/RAID	4x SATA 6Gb/s Ports and 2x SATA 3Gb/s Ports		
Integrated Gigabit	1x Realtek® 8111F Gigabit LAN Controller		
Expansion Slots	1x PCIe 3.0/2.0 x16 Slot, 1x PCIe 2.0 x16 (x4 mode) Slot, 1x PCIe 2.0 x1 Slot, 1x PCI Slot		
Integrated Super I/O	1x PS/2 Keyboard (purple) 1x PS/2 Mouse (green) 1x DVI-D Port 1x D-Sub Port 1x DisplayPort 1x HDMI Port 1x LAN (RJ45) Port 2x USB 3.0 Rear Ports 6x USB 2.0 (4x Rear, 2x Front) Ports 1x Audio Jack		
Security	Optional TPM 2.1 with On-Board Header		
Drive Bays	External: 2x 5.25" Bays & 1x 3.5" Bay (can also be used for a 3.5" internal drive) Internal: 1x 3.5" Bay & 1x 2.5" Bay	External: 1x 5.25" Bay Internal: 1x 3.5" Bay & 1x 2.5" Bay	External: 1x 5.25" Slim ODD Bay & 1x 3.5" FDD Bay Internal: 2x 2.5" Bays
Dimensions (H x W x D)	15.75" x 7.8" x 14.6" / 400mm x 198mm x 370mm	13.8" x 4.4" x 15.4" / 350mm x 112mm x 390mm	12.7" x 3.5" x 12.8" / 322mm x 90mm x 326mm
Power Supply	Input Voltage: 100-240 VAC Input Frequency: 50/60 Hz Minimum Output: 350 Watt 80 PLUS Certified Form Factor: ATX12V v2.2 Power Factor Correction: Active PFC Efficiency: >80% at Normal Input Voltage	Input Voltage: 100-240 VAC Input Frequency: 50/60 Hz Minimum Output: 300 Watt 80 PLUS Certified Form Factor: TFX12V v2.31 Power Factor Correction: Active PFC Efficiency: >80% at Normal Input Voltage	Input Voltage: 100-240 VAC Input Frequency: 50/60 Hz Minimum Output: 300 Watt 80 PLUS Certified Form Factor: TFX12V v2.31 Power Factor Correction: Active PFC Efficiency: >80% at Normal Input Voltage
Regulatory & Product Certifications	EMI/RFI: FCC Declaration of Conformity (DoC) Safety: Underwriter Laboratories (UL) 60950, 3rd Edition EPA: Energy Star Compliant; EPEAT Silver Compliant Other: NIST 800-147 Complaint BIOS		
Fans	1x 120mm Rear Cooling Fan	1x 60mm Rear Cooling Fan	None



7669 Limestone Drive
Gainesville, VA 20155
Toll-Free: 1 (888) RING-NCS
Voice: (703) 743-8500 / Fax: (703) 621-1701
www.ncsf.com

Actual functionality may be limited to other factors, including type, number and capabilities of optional modules incorporated. NCS may make changes to product specifications at any time and without notice. The information in this document is for informational use only, is subject to change without notice. NCS assumes no responsibility or liability for any errors or inaccuracies that may appear. All names are provided for informational use only. Other brands and names may be claimed as property of their respective owners.

DS-7280-03-062614