



Stratus 9170 Desktop Series

The Stratus 9170 Desktop Series offers breakthrough performance, enhanced manageability, and security for your most demanding business needs.

The Stratus 9170 Desktop Series features great expandability options with USB 3.0, SATA 6.0 Gb/s, Ethernet LAN, memory and PCI Express controllers integrated to enable 2-channel (4 DIMM up to 32GB) DDR3 memory, and 16 PCI Express 3.0 lanes. With three convenient form factors to choose from (the MT, DT, & SFF), the Stratus 9170 Desktop Series gives you an infinite number of ways to customize a desktop to suit your exact requirements. Additionally, the Stratus Desktops' tool-less chassis offers simple and direct access to system components and upgrades.

Integrated Security and Control

The Stratus 9170 Desktop Series features Intel® Core™ vPro™ Technology, which is designed to deliver cost savings and control for businesses while improving security and remote manageability. Unlike software-only solutions, these advantages are built right into the processor, chipset, and network adapters, which allow a variety of management, security, and power saving options that are otherwise impossible.

Excellent Video Quality Already Included, But Don't Be Afraid to Kick it up a Notch

The Stratus 9170 Desktop Series' integrated Intel® HD Graphics delivers superb visual performance for sharper images, richer color, and life-like video (without the extra expense of add-in video cards or decoders). The Stratus 9170 Desktop Series' also gives users the ability to multi-task on up to the independent displays through DisplayPort, HDMI and DVI-I connectors, and supports AMD Quad-GPU CrossFireX™ Technology.

Ready & Willing

The Stratus 9170 Desktop Series is also Windows® 8 ready, so your desktop runs faster, is more secure and more reliable, which can aid in maintaining high office productivity.

Stratus 9170 Desktop Series

Processor	LGA-1150 Socket: Support for 2nd, 3rd & 4th Generation Core™ i3/i5/i7, Intel® Celeron™ & Pentium™ Processors		
Chipset	Intel® Q87 Express Chipset		
System Memory	4x 240-Pin Dual Channel DIMM Sockets supporting non-ECC 1333/1600MHz DDR3 SDRAM Memory; Up to 32GB Maximum Memory Capacity		
Integrated Video	Intel® HD Graphics Multi-VGA Output Support : HDMI/DVI/DisplayPort Ports Supports VGA with a Max. Resolution of 1920x1200 Supports DVI-D with a Max. Resolution of 1920x1200 (DVI-D Port Does Not Support D-Sub Connection by Adapter) Supports HDMI with a Max. Resolution of 4096x2160 (Support for HDMI 1.4a Version) Supports DisplayPort with a Max. Resolution of 3840x2160 DisplayPort Does Not Support Other Types Of Display Connections By Adapter; Support for DisplayPort 1.2 Version. Maximum Shared Memory of 1GB Supports AMD CrossFire™ Technology		
Integrated Audio	Integrated REALTEK® ALC887 CODEC 8-Channel (7.1) High Definition Audio Front Panel Connectors: Headphone & Microphone In; Back Panel Connectors: Line-in, Line-out and Microphone-in		
Integrated Super I/O	6x USB 2.0 Ports (2x in the front and 4x in the rear) 4x USB 3.0 Ports (2x in the front and 2x in the rear) 2x PS/2 Ports, 1x RJ-45 1x DisplayPort, 1x HDMI Port, 1x VGA Port, 1x DVI-D Port 1x Optical S/PDIF Out Connector 6x Audio Jacks (Center/Subwoofer Speaker Out, Rear Speaker Out, Side Speaker Out, Line In, Line Out, Mic In)		
Integrated SATA/RAID	6x SATA 6Gb/s Connectors (SATA3 0-SATA3 5) Supporting up to 6x SATA 6Gb/s Devices Support for RAID 0, RAID 1, RAID 5, and RAID 10		
Integrated Gigabit	Intel® GbE (10/100/1000 Mbit) LAN		
Expansion Slots	1x PCI Express x16 Slot, 1x PCI Express x16 Slot (electrically x4), 1x PCI Express x1 Slot, 1x PCI Slot (<i>DT & SFF Supports Only Low Profile Expansion Cards</i>)		
Available Form Factors	MT	DT	SFF
Drive Bays	External: 2x 5.25" Bays & 1x 3.5" Bay (can also be used for a 3.5" internal drive) Internal: 1x 3.5" Bay & 1x 2.5" Bay	External: 1x 5.25" Bay Internal: 1x 3.5" Bay & 1x 2.5" Bay	External: 1x 5.25" Slim ODD Bay & 1x 3.5" FDD Bay Internal: 2x 2.5" Bays
Dimensions (H x W x D)	15.75" x 7.8" x 14.6" / 400mm x 198mm x 370mm	13.8" x 4.4" x 15.4" / 350mm x 112mm x 390mm	12.7" x 3.5" x 12.8" / 322mm x 90mm x 326mm
Power Supply	Input Voltage: 100-240 VAC Input Frequency: 50/60 Hz Minimum Output: Integrated 300W and Above Form Factor: ATX12V v2.2 Power Factor Correction: Active PFC Efficiency: >80% at Normal Input Voltage	Input Voltage: 100-240 VAC Input Frequency: 50/60 Hz Minimum Output: 300W TFX 80+ Bronze Form Factor: TFX12V v2.31 Power Factor Correction: Active PFC Efficiency: >80% at Normal Input Voltage	Input Voltage: 100-240 VAC Input Frequency: 50/60 Hz Minimum Output: Integrated 300W TFX 80+ Bronze Form Factor: TFX12V v2.31 Power Factor Correction: Active PFC Efficiency: >80% at Normal Input Voltage
Regulatory & Product Certifications	EMI/RFI: Safety: EPA: Other:	FCC Declaration of Conformity (DoC) Underwriter Laboratories (UL) 60950, 3rd Edition Energy Star Compliant; EPEAT Silver Compliant NIST 800-147 Complaint BIOS	
Fans	1x 120mm Rear	1x 60mm Rear	None



7669 Limestone Drive
 Gainesville, VA 20155
 Toll-Free: 1 (888) RING-NCS
 Voice: (703) 743-8500 / Fax: (703) 621-1701
www.ncsf.com

Actual functionality may be limited to other factors, including type, number and capabilities of optional modules incorporated. NCS may make changes to product specifications at any time and without notice. The information in this document is for informational use only, is subject to change without notice. NCS assumes no responsibility or liability for any errors or inaccuracies that may appear. All names are provided for informational use only. Other brands and names may be claimed as property of their respective owners.

DS-9172-03-062014